

First Choice High Gloss Enamel

First Choice High Gloss Enamel is a cost effective alkyd based gloss enamel paint specifically formulated for the **contracting market**. It has regular obliteration, gloss and durability.

USES:

First Choice High Gloss Enamel is for interior or exterior use on a wide range of suitably primed substrates eg. wood, steel, masonry, P.V.C. and glass.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

The following undercoats and/or primers should be applied before re-coating with two coats of First Choice High Gloss Enamel:

1. Ferrous Steel - One coat of either Warrior One Pack Etch Primer or Warrior Metal Etch Primer and then over coated with one coat of First Choice Universal Undercoat.
2. Galvanised Steel - One coat of either Warrior One Pack Etch Primer or Warrior Metal Etch Primer and then over coated with one coat of First Choice Universal Undercoat.
3. Wood - One coat Warrior Wood Primer and one coat First Choice Universal Undercoat.
4. Masonry - One coat First Choice Alkali Resistant Plaster Primer and one coat First Choice Universal Undercoat
5. P.V.C. or Glass - One coat First Choice Universal Undercoat.

PROPERTIES:

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Mineral Turpentine
THINNING SOLVENT:	Mineral Turpentine
SPREADING RATE:	PRIMER COAT : N/A FINAL COAT : 8-10 m ² per litre
DRYING TIMES:	SURFACE DRY : 4 hours HARD DRY : overnight OVERCOATING :16 hours
PACK SIZE:	1L and 5L
COLOUR RANGE:	It is important that this product be thoroughly mixed with a flat paddle before use White, Black, Golden Brown and Cream
SPECIFIC GRAVITY:	1,02 + 0,05 kg per litre
VISCOSITY:	70-75 KU
FLASH POINT:	>35°C
FINISH:	Gloss