

SECTION 1: Identification

1.1. Product identifier

| | |
|-----------------|--|
| Product form | : Mixture |
| Trade name | : First Choice Water Based Alkali Resistant Plaster Primer |
| Type of product | : Water-based paints |
| Product code | : GFP10 |
| Product group | : Trade product |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|------------------------------|------------------------|
| Use of the substance/mixture | : COATING AND PAINTING |
|------------------------------|------------------------|

1.3. Supplier's details

Manufacturer

Warrior Paints & Coatings
 45 Frans du Toit Street
 P.O. Box 911-1181
 0200 Rosslyn, Pretoria - South Africa
 T 12 5413596 - F +27 12 5411434
info@warriorpaints.co.za - www.warriorpaints.co.za

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

| | |
|---|------|
| Flammable liquids, Category 3 | H226 |
| Specific target organ toxicity — single exposure, Category 1 | H370 |
| Hazardous to the aquatic environment — Acute Hazard, Category 3 | H402 |
| Full text of H statements : see section 16 | |

2.2. Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA) :



GHS02

GHS08

| | |
|-----------------------------------|---|
| Signal word (GHS-ZA) | : Danger |
| Hazardous ingredients | : Heavy Aromatic Petroleum Solvent |
| Hazard statements (GHS-ZA) | : H226 - Flammable liquid and vapour. H370 - Causes damage to organs. H402 - Harmful to aquatic life |
| Precautionary statements (GHS-ZA) | : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor. P321 - Specific treatment (see supplemental first aid instruction on this label) |

First Choice Water Based Alkali Resistant Plaster Primer

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Flammable liquid and vapour, Causes damage to organs, Harmful to aquatic life

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to the United Nations GHS |
|-----------------------------------|----------------------|------------|--|
| Medium Aliphatic Petroleum Spirit | (CAS-No.) 64742-88-7 | 1.5 - 4 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. Not classified (Inhalation:dust,mist) STOT SE 2, H371 Aquatic Acute 2, H401 |
| Heavy Aromatic Petroleum Solvent | (CAS-No.) 64742-95-5 | 0.3 - 1.25 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 STOT SE 1, H370 Aquatic Chronic Not classified |
| Biocide | | 0.1 - 0.3 | Aquatic Acute 2, H401 |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

First Choice Water Based Alkali Resistant Plaster Primer

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|-------------------------|---|
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-------------------------------|--|
| Precautions for safe handling | : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--------------------|--|
| Technical measures | : Ground/bond container and receiving equipment. |
| Storage conditions | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Environmental exposure controls | : Avoid release to the environment. |

8.3. Individual protection measures, such as personal protective equipment (PPE)

| | |
|--------------------------|--|
| Hand protection | : Protective gloves |
| Eye protection | : Safety glasses |
| Skin and body protection | : Wear suitable protective clothing |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment |

Personal protective equipment symbol(s):



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---------------------|
| Physical state | : Liquid |
| Appearance | : Liquid. |
| Colour | : No data available |
| Odour | : No data available |
| Odour threshold | : No data available |
| pH | : 8 - 9 |
| pH solution | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Relative evaporation rate (ether=1) | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : > 65 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Not applicable |
| Vapour pressure | : No data available |
| Vapour pressure at 50 °C | : No data available |

First Choice Water Based Alkali Resistant Plaster Primer

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|---|---------------------|
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Relative density of saturated gas/air mixture | : No data available |
| Density | : 1.3 - 1.5 kg/l |
| Relative gas density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |
| Lower explosive limit (LEL) | : No data available |
| Upper explosive limit (UEL) | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| Biocide | |
|--|---------------------|
| LD50 oral rat | > 2500 mg/kg |
| LD50 dermal rat | > 2000 mg/kg |
| LC50 inhalation rat (Vapours - mg/l/4h) | 5.71 mg/l/4h |
| Medium Aliphatic Petroleum Spirit (64742-88-7) | |
| LD50 oral rat | 5000 mg/kg |
| LD50 dermal rabbit | 2000 mg/kg |
| LC50 inhalation rat (mg/l) | 5.28 mg/l/4h |
| Heavy Aromatic Petroleum Solvent (64742-95-5) | |
| LD50 oral rat | 512 - 6631 mg/kg |
| LD50 dermal rat | 2000 mg/kg |
| LD50 dermal rabbit | 5000 ml/kg |
| LC50 inhalation rat (ppm) | 5922 - 6700 ppmv/4h |

| | |
|-----------------------------------|-------------------------------|
| Skin corrosion/irritation | : Not classified pH: 8 - 9 |
| Serious eye damage/irritation | : Not classified pH: 8 - 9 |
| Respiratory or skin sensitisation | : Not classified |

First Choice Water Based Alkali Resistant Plaster Primer

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| | |
|------------------------|----------------------------|
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Causes damage to organs. |

| Medium Aliphatic Petroleum Spirit (64742-88-7) | |
|--|----------------------|
| NOAEL (oral, rat) | 750 mg/kg bodyweight |
| NOAEC (inhalation, rat, vapour) | 24 |

| Heavy Aromatic Petroleum Solvent (64742-95-5) | |
|---|----------------------------|
| LOAEL (oral, rat) | 25 - 1250 mg/kg bodyweight |
| LOAEL (dermal, rat/rabbit) | 165 mg/kg bodyweight |
| NOAEL (oral, rat) | 4 - 750 mg/kg bodyweight |
| NOAEL (dermal, rat/rabbit) | 495 mg/kg bodyweight |

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

| | |
|--------------------------|----------------------------|
| Ecology - general | : Harmful to aquatic life. |
| Acute aquatic toxicity | : Harmful to aquatic life. |
| Chronic aquatic toxicity | : Not classified |

| Biocide | |
|----------------|----------|
| LC50 fish 1 | 6.4 mg/l |
| EC50 Daphnia 1 | 32 mg/l |

| Medium Aliphatic Petroleum Spirit (64742-88-7) | |
|--|----------|
| LC50 fish 1 | 8.1 mg/l |
| EC50 Daphnia 1 | 6 mg/l |
| ErC50 (algae) | 9.4 mg/l |

| Heavy Aromatic Petroleum Solvent (64742-95-5) | |
|---|------------------|
| LC50 fish 1 | 0.58 - 8.41 mg/l |
| EC50 Daphnia 1 | 760 - 4700 µg/l |
| NOEC chronic fish | 5.6 mg/l |

12.2. Persistence and degradability

| First Choice Water Based Alkali Resistant Plaster Primer | |
|--|-------------------------------------|
| Persistence and degradability | No additional information available |

12.3. Bioaccumulative potential

| First Choice Water Based Alkali Resistant Plaster Primer | |
|--|-------------------------------------|
| Bioaccumulative potential | No additional information available |

12.4. Mobility in soil

| First Choice Water Based Alkali Resistant Plaster Primer | |
|--|-------------------------------------|
| Mobility in soil | No additional information available |

12.5. Other adverse effects

| | |
|-----------------------|---------------------------------------|
| Ozone | : Not classified |
| Other adverse effects | : No additional information available |

SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|-------------------------|---|
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information | : Flammable vapours may accumulate in the container. |

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

| SANS | IMDG | IATA |
|-----------------------------|------|------|
| 14.1. UN number | | |
| Not regulated for transport | | |

First Choice Water Based Alkali Resistant Plaster Primer

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

| SANS | IMDG | IATA |
|---|---|------------------------------------|
| 14.2. Proper Shipping Name | | |
| Not applicable | Not applicable | Not applicable |
| 14.3. Transport hazard class(es) | | |
| Not applicable | Not applicable | Not applicable |
| Not applicable | Not applicable | Not applicable |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| Dangerous for the environment : No | Dangerous for the environment : No : | Dangerous for the environment : No |
| No supplementary information available | | |

14.6. Special precautions for user

- SANS

No data available

- IMDG

No data available

- IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Date of issue : 22/04/2021

Full text of H-statements:

| | |
|------|-------------------------------|
| H226 | Flammable liquid and vapour. |
| H303 | May be harmful if swallowed |
| H312 | Harmful in contact with skin. |
| H370 | Causes damage to organs. |
| H371 | May cause damage to organs. |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |

SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product