



TDS 1.1
WARRIOR GENERAL PURPOSE ACRYLIC PVA

DESCRIPTION:

Warrior General Purpose Acrylic PVA is a low odour matt acrylic paint for interior or exterior use with good filling and obliterating properties. It is ideal for use by contractors on projects where an economic finish with limited washability is required.

USES:

Warrior General Purpose Acrylic PVA has been specifically formulated for affordable housing, garages, concrete fencing and areas where economy is most important. Warrior General Purpose Acrylic PVA can also be used as a first coat on raw plaster or as a ceiling paint.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

- a) New Masonry Surfaces: All surfaces must be dry, free of dust, dirt, grease and other surface contamination. Apply one coat of Warrior General Purpose Acrylic PVA or Warrior Water Based Alkali Resistant Plaster Primer and allow to dry for 4-6 hours. Finish with 2 coats of Warrior General Purpose Acrylic PVA to colour of choice.
- b) Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with Warrior General Purpose Acrylic PVA or Warrior Water Based Alkali Resistant Plaster Primer. All metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer. Gloss or sheen paints must always be sanded down with a fine abrasive to provide a good key for subsequent coats and then primed with one coat of Warrior Universal Undercoat. Finish off with 2 coats of Warrior General Purpose Acrylic PVA to colour of choice. Allow 4 hours drying time between coats.

PROPERTIES:

APPLICATION:	Brush, Roller, Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: 4-6 m ² per litre TOP COATS: ± 6-8 m ² per litre per coat
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 3-4 hours OVERCOATING: 4 hours
PACK SIZE:	5L, 20L
COLOUR RANGE:	White and a select range of Pastel colours
VISCOSITY:	120-130 Krebs Units (KU)
FLASH POINT:	Non flammable
SCRUB RESISTANCE:	± 3000 Oscillations
RELATIVE DENSITY:	1, 50 ± 0, 05 kg per litre
FINISH:	Matt



GENERAL INFORMATION:

*For spray application consult our Technical Department.

- a) It is important that this product be thoroughly mixed with a flat paddle before use.
- b) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.
- c) Do not wash the paint for 7 days after painting.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za