



**TDS 1.8**  
**WARRIOR BATHROOM & KITCHEN**

**DESCRIPTION:**

Warrior Bathroom & Kitchen is a water-based paint, which is highly washable, stain resistant, tough and durable with a luxurious sheen finish for interior use.

It has been formulated as a world class low odour, low VOC product with excellent steam and mould resistant properties. Warrior Bathroom & Kitchen has a VOC content of less than 16g/L when used as white or a pastel colour

**USES:**

Warrior Bathroom & Kitchen is an excellent paint specifically formulated for use on walls and ceilings in Kitchens, Bathrooms and high traffic areas. Due to its outstanding adhesive properties Warrior Bathroom & Kitchen, is ideal for overcoating previously painted sound surfaces including conventional solvent based alkyd enamels.

**SPECIFICATION OR RECOMMENDED PAINT SYSTEM:**

- a) New Masonry Surfaces: All surfaces must be dry, free of dust, dirt, grease and other surface contamination. Apply one coat of Warrior Water Based Alkali Resistant Plaster Primer and allow to dry for 6 hours.
- b) Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with Warrior Water Based Alkali Resistant Plaster Primer and allow to dry for 6 hours. All metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer and allow to dry for 6 hours. Remove all mould with Warrior Anti-Fungal Wash as per specification. Fill all imperfections with Warrior Ready Mixed Filler as per specifications. Spot prime all filled areas with Warrior Alkali Resistant Plaster Primer and allow to dry for 6 hours.
- c) New Galvanised and ferrous steel surfaces: Degrease surface and then prime with one coat of Warrior Metal Etch Primer.
- d) Wooden Surfaces: Apply one coat of Warrior Pink Wood Primer. Allow to dry for 16 hours. Finish with at least 2 coats of Warrior Bathroom & Kitchen in colour of choice. Allow 4 hours drying time between coats.  
Gloss or semi-gloss surfaces must be lightly sanded with a fine abrasive to provide a good key for subsequent coats. Thereafter wash with sugar soap.

**PROPERTIES:**

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: N/A TOP COATS: ± 8-10 m <sup>2</sup> per litre per coat
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 4 hours OVERCOATING: 4 hours
SCRUB RESISTANCE:	Washable (>10 000 Oscillations)
PACK SIZE:	1L, 2.5L , 5L, 20L
COLOUR RANGE:	White, pastel and medium colours
RELATIVE DENSITY	1.24kg/l
VISCOSITY:	120-125 ku
FLASH POINT:	Non flammable
FINISH:	Sheen



**GENERAL INFORMATION:**

\*For spray application consult our Technical Department.

- a) It is important that this product be thoroughly mixed with a flat paddle before use.
- b) Do not wash the paint for 7 days after painting.
- c) For best results allow the painted area to dry for 48 hours prior to showering or bathing. Where excessive steaming takes place it is advisable to apply a maintenance coat every 3 years.
- d) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)