



TDS 5.2
WARRIOR PINK WOOD PRIMER

DESCRIPTION:

Warrior Pink Wood Primer is an Alkyd/Oil based wood primer which penetrates and seals the wood providing an excellent primed surface for subsequent decorative finishes. It provides an excellent balance between filling, penetration and adhesion and is easy to apply.

USES:

Warrior Pink Wood Primer is an excellent wood primer for use on all types of interior/exterior surfaces.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

Ensure the wood surface to be primed is clean and dry, free from dust, oils and grease etc. Apply one coat of Warrior Pink Wood Primer, leave to dry for 24 hours, then sand lightly for a smooth finish. Dust off and apply two coats of the Warrior finishing product of your choice as per specification.

PROPERTIES:

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Mineral Turpentine
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: 6-8m ² per litre (depending on surface porosity)
	TOP COAT: N/A
DRYING TIMES:	SURFACE DRY: 4 hours
	TOUCH DRY: 16 hours
	OVERCOATING: 16 hours
PACK SIZE:	1L, 5L,
COLOUR RANGE:	Pink only
SPECIFIC GRAVITY:	1, 2 ± 0, 05 kg per litre
VISCOSITY:	75-80 KU
FLASH POINT:	>35°C
FINISH:	Matt



GENERAL INFORMATION:

*For spray application, contact our Technical Department.

- a) This product may be over coated with conventional decorative enamels and undercoats.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.
- c) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za