



TDS 5.3
WARRIOR STONE SEALER

DESCRIPTION:

Warrior Stone Sealer is a solvent based acrylic coating which is simple to use, quick drying, and offers excellent resistance to yellowing and alkaline attack. It enhances the natural colour to the substrate and restores depth, giving an attractive gloss and long lasting finish.

USES:

Warrior Stone sealer can be applied as an interior or exterior sealer on a wide range of masonry surfaces e.g. Brickwork, paving and concrete floors

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

New masonry surfaces: Ensure that the surface is dry, free from all forms of dirt, sand and loose plaster or cement. Apply two coats of Warrior Stone Sealer with a drying time of 16 hours between coats.

Surfaces previously painted with Warrior Stone Sealer:

Ensure that the surface is dry, free from all forms of dirt. A maintenance coat should be applied every 18 months.

PROPERTIES:

APPLICATION:	Brush, Roller, and Spray*
CLEANING SOLVENT:	E thinners
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: 6-8m ² per litre TOP COATS: 8-10m ² per litre
DRYING TIMES:	SURFACE DRY: 2 hour TOUCH DRY: 16 hours OVERCOATING: 16 hours
PACK SIZE:	1L, 5L
COLOUR RANGE:	Clear only
FLASH POINT:	>9°C
VISCOSITY:	15-17 sec F4
SPECIFIC GRAVITY:	0,91 ± 0,05 kg per litre
FINISH:	Gloss



GENERAL INFORMATION:

*For spray application, contact our Technical Department.

- a) Surfaces must be completely dry as any residual moisture in the substrate can result in blistering.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.
- c) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za