



TDS 6.2
WARRIOR ROAD MARKING PAINT

DESCRIPTION:

Warrior Road Marking Paint is an alkyd based, quick drying coating with a matt finish.

USES:

Warrior Road Marking Paint can be used for marking bituminous/tar, asphalt and concrete surfaces.

SPECIFICATION OR RECOMMEND PAINT SYSTEM:

The surface to be coated must be clean, free from dirt, dust, oil and grease etc. Apply two coats of Warrior Road Marking Paint and leave to dry for as long as is practically possible. It must be noted that the longer the paint is allowed to dry and the rougher the surface to be coated, the longer the paint will last. The paint will be touch dry within 10 minutes. For application to bituminous/tar, asphalt, concrete surfaces and existing road marking, priming is not necessary.

PROPERTIES:

APPLICATION:	Brush (small areas), Roller, Conventional Spray, Airless spray
CLEANING SOLVENT:	Warrior 'E' Thinners
THINNING SOLVENT:	Warrior 'E' Thinners
SPREADING RATE:	PRIMER COAT: 6-8 m ² per litre (depending on surface) TOP COATS: 8 m ² per litre
DRYING TIMES:	No pick-up time: 20 min TOUCH DRY: 45 min OVERCOATING: 45 min
PACK SIZE:	1L, 5L, 20L
COLOUR RANGE:	White, Yellow Red and Black
SPECIFIC GRAVITY:	1, 2 ± 0, 05 kg per litre
VISCOSITY:	80-90 KU
FLASH POINT:	>9°C
FINISH:	MATT



GENERAL INFORMATION:

- a) Clean all equipment immediately after use with Warrior 'E' Thinners.
- b) This material is supplied ready for application by brush or roller. For conventional spray application thin (10-15%) by volume with Warrior 'E' Thinners.
- c) It is important that this product be thoroughly mixed with a flat paddle before use.
- d) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za