



TDS 8.10
WARRIOR FIBRE FILLER

DESCRIPTION:

Warrior Fibre Filler is a tough flexible ready mixed filler for interior or exterior use. Warrior Fibre Filler contains non-toxic cellulose fibres which fill deep cracks or holes.

USES

Warrior Fibre Filler is used to fill plaster, bricks, wood, fibre cement or any other commonly used masonry substrate. It is easy to use and offers excellent adhesion and durability.

RECOMMENDED APPLICATION:

- Stir before use.
- Cracks should be opened up to assist application and adhesion.
- All areas to be filled should be clean, dry, dust free and primed with Warrior Water Based Alkali Resistant Plaster Primer or Warrior Universal Undercoat before filling.
- Warrior Fibre Filler should be applied by pushing the filler firmly into the crack with a putty knife, scraper or trowel in layers not exceeding 10mm and allowed to dry. The filler should be smoothed flush with the surface while still wet, as sanding will be difficult once dry.
- Cracks or holes deeper than 10mm should be filled in stages, allowing the first application to dry for 6 hours before applying the next application up to a total combined depth of 20mm. When complete allow to dry for a further 6 hours.
- Once dry, the surface can be sanded flush with the substrate.
- Prime with Warrior Water Based Alkali Resistant Plaster Primer prior to painting.
- Use water for cleaning.

PROPERTIES:

APPLICATION:	Putty knife, scraper or steel trowel
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	Maximum thickness of 10mm per application
DRYING TIMES:	Hard Dry: 6 hours Overcoating: 6 hours
PACK SIZE:	750g, 1.75kg, 7.5kg
COLOUR RANGE:	White
VISCOSITY:	Thick paste
FLASH POINT:	Non flammable
RELATIVE DENSITY:	± 1,75 kg per litre



GENERAL INFORMATION:

- a) Store in a cool dry place away from direct sunlight.
- b) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za