



**TDS 8.11**  
**WARRIOR RUST CONVERTER & PRIMER**

**DESCRIPTION:**

Warrior Rust Converter & Primer neutralises and converts red rust on mild steel preventing further rusting and is suitable for interior and exterior surfaces.

**USES:**

Warrior Rust Converter & Primer is for use on mild steel surfaces where it is difficult to completely remove rust. It is suitable for use on any type of structural steel such as carports, gates, fences, weathered galvanised steel etc.

**SPECIFICATION OR RECOMMENDED PAINT SYSTEM:**

**Surface Preparation:**

Ensure surface to be coated is clean and dry, free from dust, oils and grease etc. Remove all loose rust by wire brushing, chipping or sanding.

**Application:**

Apply one full coat of Warrior Rust Converter & Primer preferably by brush, ensuring that the product is thoroughly worked into the rusted area. May be overcoated with either water based paints or alkyd based paints. For additional corrosion protection apply a second coat of Warrior Rust Converter & Primer prior to application of topcoat.

**PROPERTIES:**

APPLICATION:	Brush
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	7 m <sup>2</sup> per litre
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 4 hours OVERCOATING: 4 hours
PACK SIZE:	500ml, 1L,
COLOUR RANGE:	Milky coloured when wet. Brown-black or clear when dry, depending on the nature of the substrate.
SPECIFIC GRAVITY:	1, 10 ± 0, 05 kg per litre
VISCOSITY:	65-75 KU
FLASH POINT:	Non flammable



**GENERAL INFORMATION:**

- a) Do not pour any unused product back into container.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.
- c) As per standard painting practices, no painting should take place if temperatures are below 10°C above 30°C or after 3pm and when rain is imminent.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)