



**TDS 8.9**  
**WARRIOR READY MIXED FILLER**

**DESCRIPTION:**

Warrior Ready Mixed Filler is a tough ready mixed filler for interior or exterior use.

**USES:**

Warrior Ready Mixed Filler is used to fill cracks or holes not exceeding 10 mm deep in plaster, bricks, wood, fibre cement or any other commonly used masonry substrate. It is easy to use and offers excellent adhesion and durability.

**RECOMMENDED APPLICATION:**

- Stir before use.
- Cracks should be opened up to assist application and adhesion.
- All areas to be filled should be clean, dry, dust free and primed with Warrior Water Based Alkali Resistant Plaster Primer or Warrior Universal Undercoat before filling.
- Warrior Ready Mixed Filler should be applied by pushing the filler firmly into the crack with a putty knife, scraper or trowel in layers not exceeding 5 mm. The surface should be smoothed while still wet. Allow 2 hours between applications. Once dry the surface can be sanded flush with the substrate.
- For cracks or holes between 6 mm and 10mm allow to dry between 4 and 24 hours.
- Warrior Ready Mixed Filler should be primed with Warrior Water Based Alkali Resistant Plaster Primer prior to painting.
- Cracks or holes deeper than 10mm can be prefilled with Warrior Fibre Filler.
- Use water for cleaning.

**PROPERTIES:**

APPLICATION:	Putty knife, scraper or steel trowel
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	Depended on surface, cracks and holes
DRYING TIMES:	HARD DRY: 2 hour OVERCOATING: 2 hours
PACK SIZE:	750G, 1.75kg, 7.5kg
COLOUR RANGE:	White
VISCOSITY:	Thick paste
FLASH POINT:	Non flammable
RELATIVE DENSITY:	± 1,75 kg per litre



**GENERAL INFORMATION:**

- a) Store in a cool dry place away from direct sunlight.
- b) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)