

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010 Date of issue:23/04/2021 Revision date:

Version: 1.0

SECTION 1: Identification

Product identifier

Product form : Mixture

Trade name : Warrior Super Gloss Enamel

Type of product : PAINT Product code : VARIOUS : Trade product Product group

Relevant identified uses of the substance or mixture and uses advised against

: COATING AND PAINTING Use of the substance/mixture

1.3. Supplier's details

Manufacturer

Warrior Paints & Coatings 45 Frans du Toit Street P.O. Box 911-1181 0200 Rosslyn, Pretoria - South Africa T 12 5413596 - F +27 12 5411434

info@warriorpaints.co.za - www.warriorpaints.co.za

Emergency telephone number

No additional information available

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable liquids, Category H226

Acute toxicity (oral), H303

Category 5

Serious eye damage/eye H320 irritation, Category 2B Specific target organ toxicity H370

- single exposure,

Category 1

Hazardous to the aquatic H401

environment — Acute

Hazard, Category 2

Full text of H statements : see section 16

Label elements

Labelling according to the United Nations GHS

Hazard pictograms (GHS-ZA)





GHS02

GHS08

Signal word (GHS-ZA)

Hazardous ingredients Driers; Medium Aliphatic Petroleum Spirit; Heavy Aromatic Petroleum Solvent; Xylene

Hazard statements (GHS-ZA) H226 - Flammable liquid and vapour. H303 - May be harmful if swallowed

H320 - Causes eye irritation H370 - Causes damage to organs.

H401 - Toxic to aquatic life

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements (GHS-ZA)

smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

05/05/2021 EN (English) 1/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor.

P312 - Call a POISON CENTER or doctor if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Adverse physicochemical, human health and environmental effects

: Flammable liquid and vapour, Causes damage to organs, Harmful if swallowed, Toxic to aquatic

life

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
Medium Aliphatic Petroleum Spirit	(CAS-No.) 64742-88-7	19.6875 - 26.64	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. Not classified (Inhalation:dust,mist) STOT SE 2, H371 Aquatic Acute 2, H401
Heavy Aromatic Petroleum Solvent	(CAS-No.) 64742-95-5	3.9375 - 8.325	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 STOT SE 1, H370 Aquatic Chronic Not classified
Xylene	(CAS-No.) 1330-20-7	1.11 - 2.05	Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. Not classified (Dermal) Aquatic Acute 1, H400
Driers		1 - 1.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302
Methyl ethyl ketoxime		0.1 - 0.4	Flam. Liq. 4, H227 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Aquatic Acute 3, H402

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you

feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : mild eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

05/05/2021 EN (English) 2/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

5.3. Advice for firefighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Clean up any spills as soon as possible, using an absorbent material to collect it. Avoid contact with skin and eyes. No open flames. No smoking. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. May be harmful to aquatic organisms, to flora, to soil organisms.

6.1.1. For non-emergency personnel

Emergency procedures

and workpits, or any place where its accumulation can be dangerous. May be harmful to aquatic organisms, to flora, to soil organisms.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Collect spillage.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information

: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Environmental exposure controls

: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves
Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):









8.4. Exposure limit values for the other components

No additional information available

05/05/2021 EN (English) 3/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.

Colour : No data available

Odour : aromatic.

Odour threshold No data available рΗ : No data available pH solution : No data available Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available : Not applicable Melting point Freezing point : No data available Boiling point : No data available

Flash point : > 35 °C

Auto-ignition temperature No data available Decomposition temperature : No data available Flammability (solid, gas) : Not applicable Vapour pressure : No data available Vapour pressure at 50 °C No data available Relative vapour density at 20 °C : No data available Relative density : No data available No data available Relative density of saturated gas/air mixture

Density : 1 - 1.1

Relative gas density No data available : No data available Solubility : No data available Log Pow No data available Log Kow Viscosity, kinematic No data available Viscosity, dynamic : No data available Explosive properties : No data available : No data available Oxidising properties **Explosive limits** : No data available Lower explosive limit (LEL) : No data available Upper explosive limit (UEL) : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : May be harmful if swallowed.

Acute toxicity (dermal) : Not classified

05/05/2021 EN (English) 4/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

coolding to OANO 10254.2000 and OANO 1101	4.2010	
Acute toxicity (inhalation)	: Not classified	
ATE ZA (oral)	4313.333 mg/kg bodyweight	
Methyl ethyl ketoxime		
LD50 oral rat	2.5 - 4 ml/kg	
LD50 dermal rat	1 - 2 ml/kg	
Driers		
LD50 oral rat	1400 mg/kg	
Medium Aliphatic Petroleum Spirit (6-	4742-88-7)	
LD50 oral rat	5000 mg/kg	
LD50 dermal rabbit	2000 mg/kg	
LC50 inhalation rat (mg/l)	5.28 mg/l/4h	
Heavy Aromatic Petroleum Solvent (64742-95-5)		
LD50 oral rat	512 - 6631 mg/kg	
LD50 dermal rat	2000 mg/kg	
LD50 dermal rabbit	5000 ml/kg	
LC50 inhalation rat (ppm)	5922 - 6700 ppmv/4h	
Xylene (1330-20-7)		
LD50 oral rat	3608 mg/kg	
LD50 dermal rabbit	14100 mg/kg	
LC50 inhalation rat (ppm)	4330 ppm/4h	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Causes eye irritation.	
Respiratory or skin sensitisation	: Not classified	
Gorm cell mutagonicity	: Not classified	

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : Causes damage to organs.

Medium Aliphatic Petroleum Spirit (64742-88-7)		
NOAEL (oral, rat)	750 mg/kg bodyweight	
NOAEC (inhalation, rat, vapour)	24	
Heavy Aromatic Petroleum Solvent (64742-95-5)		
LOAEL (oral, rat)	25 - 1250 mg/kg bodyweight	
LOAEL (dermal, rat/rabbit)	165 mg/kg bodyweight	
NOAEL (oral, rat)	4 - 750 mg/kg bodyweight	
NOAEL (dermal, rat/rabbit)	495 mg/kg bodyweight	

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1	Tox	icit	ty

Ecology - general : Toxic to aquatic life.

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Not classified

Methyl ethyl ketoxime	
LC50 fish 1	46 mg/l
EC50 Daphnia 1	750 mg/l
EC50 72h algae (1)	83 mg/l

Medium Aliphatic Petroleum Spirit (64742-88-7)	
LC50 fish 1	8.1 mg/l
EC50 Daphnia 1	6 mg/l
ErC50 (algae)	9.4 mg/l

Heavy Aromatic Petroleum Solvent (64742-95-5)	
LC50 fish 1	0.58 - 8.41 mg/l
EC50 Daphnia 1	760 - 4700 μg/l

05/05/2021 EN (English) 5/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

Heavy Aromatic Petroleum Solvent (64742-95-5)			
NOEC chronic fish	5.6 mg/l		
Xylene (1330-20-7)			
LC50 fish 1	16.1 (2.6 - 8.4) mg/l		
EC50 Daphnia 1	5 mg/l		
EC50 other aquatic organisms 1	1 mg/l		
EC50 72h algae (1)	4.7 mg/l		
12.2. Persistence and degradability			
Warrior Super Gloss Enamel	Warrior Super Gloss Enamel		
Persistence and degradability	No additional information available		
12.3. Bioaccumulative potential			
Warrior Super Gloss Enamel			
Bioaccumulative potential	No additional information available		
12.4. Mobility in soil			
Warrior Super Gloss Enamel			
Mobility in soil	No additional information available		
12.5. Other adverse effects			
Ozone	: Not classified		
Other adverse effects	· No additional information available		

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. Proper Shipping Name		
Paint	Paint	Paint
14.3. Transport hazard class(es)		
3	3	3
3	3	Not applicable
14.4. Packing group		l
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
	:	
No supplementary information available		

14.6. Special precautions for user

- SANS

No data available

- IMDG

No data available

- IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

05/05/2021 EN (English) 6/7

Safety Data Sheet

According to SANS 10234:2008 and SANS 11014:2010

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

SECTION 16: Other information

Date of issue : 23/04/2021

Full text of H-statements:

Flammable liquid and vapour.
Combustible liquid
Harmful if swallowed.
May be harmful if swallowed
Harmful in contact with skin.
Causes eye irritation
Causes damage to organs.
May cause damage to organs.
Very toxic to aquatic life.
Toxic to aquatic life
Harmful to aquatic life

SDS South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

05/05/2021 EN (English) 7/7