



**TDS 1.5**  
**WARRIOR HI HIDING CONTRACTORS PVA**

**DESCRIPTION:**

Warrior Hi Hiding Contractors P.V.A is a heavy bodied acrylic P.V.A specifically formulated for the Builders/Contractors market as an economical first and or finishing coat. It has excellent filling properties, very good whiteness when dry and is easy to apply.

**USES:**

Warrior Hi Hiding Contractors P.V.A may be used as a first coat or as a final coat. First coat application would be on raw plaster, while final coat application would be for ceilings boundary walls, garages, etc. This product is used extensively on affordable housing projects.

**SPECIFICATION OR RECOMMENDED PAINT SYSTEM:**

New Plaster: Ensure that surface to be coated is clean and dry. Apply one coat Warrior Hi Hiding Contractors PVA or Warriorfill as an undercoat, leave to dry for  $\pm$  4 hours, and then apply two coats Warrior Hi Hiding Contractors P.V.A allowing 4 hours drying time between coats.

Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with Warrior Hi Hiding Contractors PVA or Warrior Water Based Alkali Resistant Plaster Primer. All metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer.

Gloss or semi-gloss acrylic paints must always be sanded down with a fine abrasive to provide a good key for subsequent coats. Enamel paints should be sanded and then primed with one coat of Warrior Universal Undercoat.

Finish off with 2 coats of Warrior Hi Hiding Contractors P.V.A to colour of choice. Allow 4 hours drying time between coats.

**PROPERTIES:**

|                   |   |
|-------------------|---|
| APPLICATION:      | Brush, Roller and Spray*  |
| CLEANING SOLVENT: | Water   |
| THINNING SOLVENT: | Do not thin - ready for use   |
| SPREADING RATE:   | PRIMER COAT: 4-6 m <sup>2</sup> per litre<br>TOP COATS: 5-7 m <sup>2</sup> per litre per coat |
| DRYING TIMES:     | SURFACE DRY: 1 hour<br>TOUCH DRY: 4 hours<br>OVERCOATING: 4 hours                             |
| PACK SIZE:        | 5L, 20L   |
| COLOUR RANGE      | White, pastel colours, Beige, Cream, Sahara, Honey, Grey Dawn, Grey Cloud and Apricot.        |
| VISCOSITY:        | 130-135 KU  |
| RELATIVE DENSITY  | 1, 40 $\pm$ 0, 05 kg per litre  |
| FLASH POINT:      | Non flammable   |



FINISH:

Matt



**GENERAL INFORMATION:**

\*For spray application consult our Technical Department.

- a) It is important that this product be thoroughly mixed with a flat paddle before use.
- b) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)